



- MAX. EFFICIENCY 98.6%
- IP65 PROTECTION

STT 4~25kW

Three Phase | 2 MPPTs | ON Grid

- High reliability due to good heat dissipation design
- Integrated lightning protection for both DC and AC
- Adapt to complex grid environments
- High anti-corrosion ability with aluminum alloy die casting technology
- Wider working temperature and altitude, adapt to various installation environments

SAFE & RELIABLE



- High yield with Max. Efficiency 98.6%
- European weighted efficiency 98.2%
- Longer working hours due to the lower start-up voltage and wider MPPT range
- Up to 10% continuous output overloading capacity
- With a max input current of 15A, compatible with high-power panels

HIGH YIELD



- Support wireless and wired internet connection (RS485, WiFi/GPRS/LAN optional)
- Remote upgrading available
- Fast and easy configuration via App or OLED display

EASY TO USE



Model	STT-4KTL-P	STT-5KTL-P	STT-6KTL-P	STT-8KTL-P	STT-10KTL-P	STT-12KTL-P	STT-15KTL-P	STT-17KTL-P	STT-20KTL-P	STT-25KTL-P
Input										
Max. Input Power (W)	6,400	8,000	9,600	12,800	16,000	19,200	24,000	27,200	32,000	40,000
Start-up Voltage (V)	180	180	180	180	180	180	180	180	180	180
Min. DC Voltage (V)	150	150	150	150	150	150	150	150	150	150
Max. DC Input Voltage (V)	1,100	1,100	1,100	1,100	1,100	1,100	1,100	1,100	1,100	1,100
Rated DC Input Voltage (V)	620	620	620	620	620	620	620	620	620	620
MPPT Voltage Range (V)	160-1000	160-1000	160-1000	160-1000	160-1000	160-1000	160-1000	160-1000	160-1000	160-1000
Number of MPP Trackers	2	2	2	2	2	2	2	2	2	2
Number of DC Inputs per MPPT	1	1	1	1	1	1	1/2	2	2	2
Max. Input Current (A)	15/15	15/15	15/15	15/15	15/15	15/15	15/30	30/30	30/30	30/30
Max. Short-circuit Current (A)	20/20	20/20	20/20	20/20	20/20	20/20	20/40	40/40	40/40	40/40
Output										
Rated Output Power (W)**	4,000	5,000	6,000	8,000	10,000	12,000	15,000	17,000	20,000	25,000
Max. Output Power (W)	4,400	5,500	6,600	8,800	11,000	13,200	16,500	18,700	22,000	25,000
Max. Apparent Power (VA)	4,400	5,500	6,600	8,800	11,000	13,200	16,500	18,700	22,000	25,000
Rated Output Voltage (V)**	3L/N/PE, 230/400V									
Rated AC Frequency (Hz)	50/60 45-55/55-65									
Max. Output Current (A)	6.7	8.4	10	13.3	16.5	20	25	28.4	31.9	39
Power Factor	0.8 leading...0.8 lagging									
THDi @ Rated Power	< 3%									
DCI	< 0.5%In									
Efficiency										
Max. Efficiency	98.1%	98.1%	98.3%	98.3%	98.6%	98.6%	98.6%	98.6%	98.6%	98.6%
Euro Efficiency	97.9%	97.9%	98.0%	98.0%	98.2%	98.2%	98.2%	98.2%	98.2%	98.2%
MPPT Efficiency	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%	99.9%
Protection										
DC Reverse Polarity Protection	Integrated									
Insulation Resistance Detection	Integrated									
DC Switch	Optional									
Surge Protection	Integrated									
Over-temperature Protection	Integrated									
Residual Current Protection	Integrated									
Anti-islanding protection	Integrated									
AC Short-circuit Protection	Integrated									
AC Over-voltage Protection	Integrated									
General Data										
Dimensions [W*H*D] (mm)	550*410*175									
Weight (kg)	23						26	29		
Protection Degree	IP65									
Self-consumption at Night (W)	< 1									
Topology	Transformerless									
Operating Temperature Range (°C)	-30~60									
Relative Humidity (%)	0~100									
Operating Altitude (m)	4000 (derating > 3000)									
Cooling	Natural Convection							Smart Fan Cooling		
Noise Level (dB)	< 25							< 40		
Display	OLED & LED									
Communication	RS485, WiFi/GPRS/LAN (Optional)									

** Due to differences in voltage values in various countries, minor variations may occur. The final interpretation rights belong to Sunways.